MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.										
IDENTITY						PART NO.				
(As shown on Label or package) Vyna Bond excluding 12oz. (F-632)							IF APPL	IF APPLICABLE		
SECTION I										
MANUFACTURER'S NAME Plasti Dip International Inc.							EMERGENCY PHONE No. 1-800-424-9300			
<u> </u>						REVISION #				
				MANUFACTURER'S PHONE						
Blaine, MN 55449					No. FOR INFORMATION 1-763-785-2156 DATE MSDS					
							RED October 7,	2003		
SECTION II - HAZARDOUS			RMATION.	All Hea	lth H	azards which comp	orise 1% or grea	ter of the compo	sition and all	
carcinogens if 0.1% of the composition or greater.										
HAZARDOUS COMPONE			% Wt.		CAS NO.	OSHA	ACGIH	OTHER LIMITS		
IDENTITY AND COM		E (S)	(OPTIONAL)			PEL	TLV	RECOMMEND		
Methyl Ethyl			80.2		78-93-3	200 ppm	200 ppm	None		
Dimethylforn			3.7			68-12-2	30 mg/m ³	30 mg/m ³	None	
Resins			16.1		N/A	N/A	N/A	None		
CRESTION HI NURSEELL	CITTERITO	I CIII D . C	TENTOTICS.							
SECTION III - PHYSICAL /										
BOILING Specific Gravity (H20 -1) POINT 175 - 282°F 0.85				5		APPROXIMATE WEIGHT PER GALLON (LBS) 7.06				
VAPOR PRESSURE	VAPOR PRESSURE VAPOR DENSITY				EVAPORATION RATE					
78 mmHg @ 20°C		,	Heavier than a		(BUTYL ACETATE = 1) >1.0					
SOLUBILITY IN WATER Insoluble		% VOLAT								
APPEARANCE		TOC LDS	JGAL 3.5			(IF AIVI)				
AND ODOR Milky white sy	yrupy liquid,	strong odor.								
SECTION IV-FIRE AND EX	PLOSION	HAZARD D	ATA							
			FLAN	AMMABLE LIMITS		LEL		UEL		
(METHOD USED) TCC		0.9 – 11.5		0.9 - 11.5	0.9		11.5			
EXTINGUISHING										
MEDIA Carbon dioxide, dry chemical, or foam.										
SPECIAL FIRE FIGHTING RECOGNITION Self-contributed by adding a contraction of the first self-contributed by adding a contributed by a contributed by adding a contributed by a contributed by adding a contributed by adding a contributed by a										
PROCEDURES Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode. UNUSUAL FIRE AND										
EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.										
HAZARDOUS PRODUCTS FORMED BY										
FIRE OR THERMAL DECOMPOSITION Carbon dioxide and/or carbon monoxide.										
EXPLOSIVE LIMITS (% BY VOLUME IN AIR) 0.9 – 11.5										
SECTION V - OPTIONAL H		ATINGS IDE	ENTIFICATION	ON						
HAZARD RATING					National Fire Protection Association (NFPA)					
4-EXTREME										
3-НІСН				FIRE 3 REACTIVITY 0 .						
2-MODERATE										
1-SLIGHT										
0-INSIGNIFICANT **SEE SECTION IV				HEALTH 2 SPECIAL HAZARDS None.						
**SEE SECTION IV										

SECTION VI - REACTIVIT	Y AND STABILITY DATA					
STABILITY UNSTAI	BLE STABLE X					
INCOMPATIBILITY (Mater	ials to Avoid) Strong acids, bases, oxidizing	agents, selected amines with alkali me	tals and halogens.			
HAZARDOUS DECOMPOSI	TION OR BY PRODUCTS					
HAZARDOUS	MAY OCCUR	CONDITIONS TO AVOID				
POLYMERIZATION	WILL NOT OCCUR X	May be ignited by heat, sparks, flam	e or static electricity			
SECTION VII - HEALTH HA	AZARD DATA					
ROUTES OF ENTRY	INHALATION? YES SKIN? YI	ES INGESTION? YES E	YES? YES			
HEALTH ACUTE	X					
HAZARDS CHRONIC	X					
CARCINOGENICITY: No						
07.0740770						
SIGNS AND	To be a first of the second of					
SYMPTOMS OF	Headache, Dizziness, Drowsiness, Fatigue,	Irregular Heartbeat, Skin and Eye Irri	ation.			
EXPOSURE						
MEDICAL CONDITIONS C	ENED ALLY ACCDAYATED BY EVDOC	LDE				
MEDICAL CONDITIONS GI	ENERALLY AGGRAVATED BY EXPOS	UKE				
EMERGENCY AND	Ingestion: Contact Physician or Poison Co	entral Immediatles				
FIRST AID	Inhalation: Remove to fresh air. Administ		Nacassani			
PROCEDURES	Eye Contact: Flush with large amounts of					
1 ROCEDCRES	Skin: Wash with soap and water.	water. If tittation persists, contact in	ystetun.			
SECTION VIII - PRECAUTI	ONS FOR SAFE HANDLING AND USE					
BECKEN VIII TREEKCTI	OND TORBITE MINDERNO MID ONE					
STEPS TO BE TAKEN	Floor may be slippery, use care to avoid fal-	lling Dike and contain snill with inert	material (sand/earth)			
IN CASE MATERIAL IS	Floor may be slippery, use care to avoid falling. Dike and contain spill with inert material (sand/earth). Transfer liquid to containers for recovery or disposal. Keep spills and runoff out of municipal sewers and open bodies of water.					
RELEASED OR	If large spill, Notify appropriate state and local agenicies.					
SPILLED						
	DDS Dispose of product in accordance with le	ocal, county, state and federal regulation	ons.			
		, , , , , , , , , , , , , , , , , , , ,				
PRECAUTIONS TO BE	Avoid eye contact with eyes. Keep contain	er closed. Use with adequate ventilati	on. Keep away from sparks, flame and heat			
TAKEN IN HANDLING	Sources and store in a cool area. Avoid inh	nalation of vapors and personal contact	with liquid product.			
AND STORAGE	Use good personal hygiene practices.					
OTHER	Keep Container Closed When Not In Use.	Containers should be disposed of in a	n environmentally safe manner in accordance			
PRECAUTIONS	with Governmental Regulations.					
SECTION IX - CONTROL M						
	ION (SPECIFY TYPE) Depending on the airl		PROTECTIVE GLOVES			
_ · · · ·	IOSH approved cartridge and connister, or su		Impervious			
VENTILATION	LOCAL EXHAUST Supplemental (if no					
	MECHANICAL (GENERAL) To Main		OTHER None			
EYE PROTECTION		PROTECTIVE CLOTHING OR E	QUIPMENT			
Chemical splash goggles or app		ous clothing/boots as needed.				
	CES Wash thoroughly after handling produ	act.				
SECTION X - TRANSPORTA						
D.O.T. PROPER SHIPPING		D.O.T. HAZARD CLAS	SS 3, PG II			
	DDITY ORM-D", WHAT IS THE HAZAR	D CLASS 3, PG II				
D.O.T. I.D. No. (N/U OR N/A)		DD CT +CC 2 DC H	TATO N. AVA			
IATA PROPER SHIPPING N		RD CLASS 3, PG II	IMO No. N/A			
SECTION XI - 313 SUPPLIE		THE TRANSPORTED TO THE COURT	A PRIVITO OF OF OF OTHER AND A CONTROL OF			
	S THE FOLLOWING CHEMICALS SUB					
1	NG AND COMMUNITY RIGHT -TO-KNOW Methyl Ethyl Ketone and Dimethylformam	, , , , , , , , , , , , , , , , , , , ,	ne on page 1 for			
<u> </u>	T CONTAINS A CHEMICAL KNOWN T		TO CAUSE CANCED AND RIDTH			
DEFECTS, OR OTHER REP		O THE STATE OF CALIFORNIA	TO CAOSE CANCER AND DIRIT			
1		ed in duplex. Page 2 of 2 pages if not o	luplex.			

Prepared By:		